

Beam Wet

LED TAPE LIGHT

DESCRIPTION

All PreciseLED tape light products feature a flexible copper core and are cut and soldered to specified length in our factory. PreciseLED tape lights additionally have best-in-class color rendering, color consistency, and, when combined with our dimming drivers, dimming and flickering performance. Our BEAM Wet Tape Light is for when compromise is not an option. With a wet location rating of IP65, there's not much this LED tape light cannot handle. The silicone sleeve is protective against Hi Stream Water Jets and is specially formulated not to change the color temperature.

SPECIFICATIONS


- Voltage: 24V
- Watts per foot: 2.93W/ft
- Average Lumens per foot: 165.5 Lm/ft
- 3528 LEDs
- 36 LED's per foot
- Dimmable using dimmable driver
- Ambient Temperature: -4°F ~ +113°F
- Humidity: 40% ~ 70% R
- Protection: IP65
- 50,000 Hours Lamp Life
- Max Run: 26.24 Feet
- 3 Step Binning Process
- CRI ≥ 95 , $R_r \geq 95$, $R_g \geq 100$
- UL Listed for US and Canada
- 5 Year Warranty
- Not Field Cuttable

ORDERING CODE

Example: **BEAW-16'-24V-95C-30K-EGNT**

Product	Spool Length	Volts	CRI	Color Temperature	Ambience
BEAW		24V	95C		
BEAW	<input type="text"/> 'ft <input type="text"/> "in Custom Length For ordering lengths, see page 2.	24V-24V	95C ≥ 95 CRI	22K 2200K 24K 2400K 27K 2700K 30K 3000K 35K 3500K 40K 4000K	STANDARD EGNITE* *For 3000K and below Click here for Egnite info.

COMPATIBLE TAPE LIGHT DRIVERS




Click [here](#) for a more detailed Driver Overview.

Project Name:
Fixture Type:



DIMENSIONS



LUMEN OUTPUT PER COLOR TEMPERATURE






2700K	140 Lm/ft
3000K	180 Lm/ft
3500K	174 Lm/ft
4000K	195 Lm/ft

Beam Wet

LED TAPE LIGHT

Project Name:

Fixture Type:

Optional Wiring Configurations	Description	Ordering Code
 <p>12"(Standard) OR Desired Length(feet)</p>	Custom Tail Wire Length	TAIW
 <p>12"(Standard) OR Desired Length(feet)</p>	Custom Lead Wire Length	LEAW
	Tail Jumper Cable	JUMP
	2.1MM DC CONNECTOR (FEMALE)	PLGF
	2.1MM DC CONNECTOR (MALE)	PLGM


*Default wire length is 12", no number in front of ordering code indicates default length

Note: Solder points are secured with cable grips.

ORDERING CODE

Example: BEAW-16'-24V-95C-30K-EGNT-14TAIW


COMPATIBLE TAPE LIGHT CHANNELS




FGRE - Figure



FGFL -
Figure Flat



CNWD -
Connectwide



45WD -
45 Degree Wide



FGTL -
Figure Tall

Click [here](#) to view our Tape Light Channels

Beam Wet


LED TAPE LIGHT

Project Name:

Fixture Type:

■ LEVEL OF SPOTLESSNESS PER CHANNEL/LENS COMBINATION

	Opal Lens	Diffuse Lens	Clear Lens
FIGURE	SL	SL	CL
FIGURE SLIM	SP	SP	CL
FIGURE FLAT	SS	SP	CL
CONNECTWIDE	SL	SS	CL
45 DEGREE	SL	SS	CL



SL = Spotless

SS = Slightly Spotty

SP = Spotty

CL = Clear

■ TOTAL LUMEN OUTPUT PER CHANNEL/LENS COMBINATION

	Opal Lens	Diffuse Lens	Clear Lens
FIGURE	30%	51%	70%
FIGURE SLIM	39%	63%	86%
FIGURE FLAT	41%	63%	85%
CONNECTWIDE	26%	53%	67%
45 DEGREE	25%	49%	62%

Beam Wet

LED TAPE LIGHT

Project Name:

Fixture Type:

TM-30 DATA

