

## Fixed Modular Downlight

### DESCRIPTION

The Novation Uno provides an elegant solution for new construction projects. Our new plaster-in-trim allows seamless ceilings with a modern look. At the core of the Uno is a combined light engine and driver, enabling easy servicing leaving the trim intact. Up to four fixtures can be modularly nested together paving the way for more intricate design.

### 12 W Output Performance\*

Color Temperature	3000K
Delivered Lumens (lm) (60° Beam Spread)	751

For options other than 12W, 30K please use the multiplier chart to calculate the output performance

Wattage	14W	12W	10W
27K Multiplier	1.12	1	.81
30K Multiplier	1.19	1	.85
35K Multiplier	1.12	1	.81
40K Multiplier	1.12	1	.81

\*Estimated Data

-  4-3/16" diameter cutout
- or
-  4-3/16" x 4-3/16" cutout

Project Name: \_\_\_\_\_


Fixture Type: \_\_\_\_\_

Notes: \_\_\_\_\_



Plaster Trim Example

### DIMENSIONS



### ORDERING CODE

**Example:** NVTN-3-UNO-16.5W-30K-90C-60D-DRIV-UNO-AT-CL-MI

Product	Watts	Color Temp	CRI	Beam Lens Spread	Driver	Housing	Accessory <sup>®</sup> (Optional)	Optional
NVTN-3-UNO Fixed Housing	10W 10 Watts 12W 12 Watts 14W 14 Watts  Custom Wattage (Max 14W)  Preliminary Data, Subject to Change	27K 2700K 30K 3000K 35K 3500K 40K 4000K	90C 90CRI	60D 60° (Default) 45D 45° 38D 38° 24D 24° <sup>(1)</sup>	Driv-Uno 0-10V, 120-277V 1% dimming; Triac/ELV*	AT -Airtight (Default) CP - ChicagoPlenum	CL Clear Lens LI Linear Lens PR Prismatic Lens SA Sanded Lens SO Softening Lens MB Micro Louver (Black) MA Micro Louver (Aluminum)	MI Micro Inverter <sup>®2</sup> CB C-Channel bars with butterfly mounting brackets for acoustical ceiling.  *Nailer bars included.

### TRIM ORDERING CODE

**Example:** NVTN-UNO-TRIM-RD-PT-WH-WH-ADPT-RD

Product	Type	Outer Finish	Inner Finish	Trim Adapter
NVTN-3 TRIM	PT-RD Round Plaster Trim CS-SQ Seried C Square Trim AS-RD Seried A Round Trim BS-SQ Seried BSquare Trim BS-RD Seried B Round Trim	WH-White BK- Black XX -Custom Powder Coating (Consult factory for colors)	WH-White BK- Black XX -Custom Powder Coating (Consult factory for colors)	ADPT-SQ-UNV-3G Use for type Square in drywall ceiling ADPT-RD-UNV-3G Use for type Square in drywall ceiling ADPT-RD-HARD-3G Use for type Square in drywall ceiling


## Fixed Modular Downlight

### TRIM COMPATIBILITY


⊕ 4-3/16" diameter cutout  
or  
⊕ 4-3/16" x 4-3/16" cutout




Requires round sheetrock cutout:  
4-3/16" Diameter




Series B  
Round Adapter




Series B  
Round Trim



Round  
Plaster Trim




Series A  
Round Collar




Series A  
Round Trim




Requires square sheetrock cutout:  
4-3/16" x 4-3/16"




Square Adapter



Series B  
Square Trim



Series C  
Square Collar






Series C  
Square Trim



### TRIM EXAMPLES






NVTN-3-TRIM-PT-RD-WH-WH





NVTN-3-TRIM-CS-SQ-WH-WH





NVTN-3-TRIM-AS-RD-WH-WH






NVTN-3-TRIM-CS-SQ-WH-BK





NVTN-3-TRIM-AS-RD-WH-BK





NVTN-3-TRIM-BS-SQ-WH






NVTN-3-TRIM-BS-RD-WH





## Fixed Modular Downlight




NVTN-3-TRIM-BS-SQ-BK



NVTN-3-TRIM-BS-RD-BK



### ■ OPTICAL ACCESSORIES



### ■ SPECIFICATIONS

#### LED SYSTEM \*

- LED ENGINE and Driver: SWM1: 2700K, 3000K, 3500K, 4000K
- LUMENS/WATTS: up to 100 Lumen/Watt (Source Lumens)
- CRI: Minimum 90 color rendering index with an option of 95 CRI
- COLOR CONSISTENCY: 2-step binning LEDs
- OPTICS: 60° beam spread lens included, 45°, 38°, lens available, field changeable, 24°. Additional optics accessories available.

#### ELECTRICAL

- Driver is integral to fixture and fully accessible from below the ceiling.
- STANDARD DRIVER: 120-277VAC, fully dimmable using 0-10V (dim down to 1%), dim to off, forward-phase (TRIAC), or reverse-phase (ELV) dimmers (TRIAC & ELV dimming only at 120VAC). Driver is fully accessible from below the ceiling.
- FEED: Standard 18-gauge Line Voltage 16-gauge Dimming conductor single circuit feed. Push-in quick connectors allow ease of driver replacement
- EMERGENCY: Remote emergency battery pack provides backup power for 90 minutes. Remote emergency test switch included.

#### MOUNTING

Residential grade nailer bars included with housing, fitted to short side of housing, extend 14" to 25" to fit different joist spacing. Accommodates to 1/2", 5/8" ceiling thickness in drywall, millwork and acoustical ceiling types.

\* Preliminary Data, subject to change.


#### CONSTRUCTION \*

- HOUSING: Heavy gauge cold rolled steel with through wire J-box
- HEAT SINK: Precision-cut extruded aluminum heat sink.
- HEAT PIPE: Vacuum-sealed copper tubes transfer heat away from the LED to heat sink.
- TRIM: Plaster
- LENS COVER: Use round lens cover for both round/square trims
- TRIM ADAPTER: Die-cast aluminum
- FINISH: Housing-Standard power-coated matte black. Trim-White, Black, Consult factory for custom power coating finish.


#### LISTING/WARRANTY \*

- WARRANTY: 5 Year Limited Warranty, Ambient temperatures at fixture location should not exceed 40° C during normal operation.
- LED LIFE > 50,000 hours at 70% lumen maintenance (L70)
- WEIGHT: 4.81 lbs

## Fixed Modular Downlight



### ■ Modular Configuration




NOTE: For perfectly square light placement separate fixture A&B from C&D by .63"

### ■ Wiring Diagram


#### Selectable White (Static Mode ) and Warm Dim

Triac Dimmer:



0-10 V Dimmer:

0-10 V CONTROLLER



## Fixed Modular Downlight

-  4-3/16" diameter cutout
- or
-  4-3/16" x 4-3/16" cutout

### ■ DIMMER COMPATIBILITY CHART

Uno Driver			
Dimmer Manufacturer	Product	Part Number	Dimming Range
Compatible 0-10V (120V/277V)			
Lutron	Diva	DVTV/DVSTV	100%-1%
Lutron	Nova	NFTV	100%-1%
Leviton	Illumatech	IP710-DL	100%-1%
Compatible TRIAC/ELV (120V Only)			
Lutron	Adriadni	TGCL-153P	100%-10%
Lutron	Diva	DVCL-153P	100%-10%
Lutron	Diva	DVRP-253P	100%-10%
Lutron	Maestro	MACL-153M	100%-10%
Lutron	Radio	RRD-PRO	100%-10%
Lutron	Skylark	SCL-153P	100%-10%
Leviton	Illumatech	DSE06	100%-10%